# Learning to Generate Structured Output with Schema Reinforcement Learning

**Anonymous ACL submission** 

#### Abstract

This study investigates the structured generation capabilities of large language models (LLMs), focusing on producing valid JSON outputs against a given schema. Despite the widespread use of JSON in integrating lan-005 guage models with programs, there is a lack of comprehensive analysis and benchmarking of these capabilities. We explore various aspects of JSON generation, such as structure understanding, escaping, and natural language description, to determine how to assess and enable 011 LLMs to generate valid responses. Building upon this, we propose SchemaBench features around 40K different JSON schemas to obtain and assess models' abilities in generating valid JSON. We find that the latest LLMs are 017 still struggling to generate a valid JSON string. 018 Moreover, we demonstrate that incorporating reinforcement learning with a Fine-grained Schema Validator can further enhance models' understanding of JSON schema, leading to improved performance. Our models demonstrate significant improvement in both generating JSON outputs and downstream tasks.

## 1 Introduction

027

Recent advancements in Large Language Models (OpenAI et al., 2023; Chowdhery et al., 2022; Touvron et al., 2023; Zeng et al., 2023) have facilitated the development of various intelligent applications like automatic web search (Qin et al., 2023a) or software development (Qian et al., 2023). Among these applications, the structured generation of outputs, represented in **JSON**<sup>1</sup> format (Chen et al., 2025; Escarda-Fernández et al., 2024), has emerged as a widely utilized feature for integrating language models with various automatic systems and pipelines, enhancing the flexibility of language models in real-world tasks.

Several methods exist for generating JSON strings from LLMs. Prompting (Pokrass et al., 2024; He et al., 2024) is a simple approach that works well for basic schemas but struggles with complex logic due to the model's limited capacity, as Figure 1 shows. Tool calls (Schick et al., 2023; Qin et al., 2023c) can convert model output into JSON, but often miss certain schema-specific syntax, leading to incomplete or incorrect results. Constraint decoding methods like Outlines (Willard and Louf, 2023) generate valid JSON independently of the model's schema capabilities but can reduce output quality (Tam et al., 2024) and are time-consuming due to the need for finite-state machines. The underlying challenge is the difficulty of generating valid JSON strings for intricate schemas, compounded by a lack of comprehensive benchmarks to evaluate model performance on such complex tasks.

040

041

042

043

044

045

047

049

053

054

058

059

060

061

062

063

064

065

066

067

068

069

070

071

072

073

074

075

076

077

078

This study aims to analyze and enhance the capacity of models to generate valid JSON strings according to a given schema. Initially, we have developed the SchemaBench comprising around 40K JSON schemas to identify primary challenges that models encounter during the generation of JSON strings. The benchmark encompasses three categories of challenges: the generation of valid JSON strings with a given JSON schema, the comprehension of instructions inherent to JSON schemas, and the escape of special tokens within JSON strings. We benchmark the latest models and find that current models are still limited in dealing with complex JSON schemas, with only 61.06% correctness on the SchemaBench. In our practice, even after supervised fine-tuning, the model still struggles to learn basic JSON syntax in some cases. This highlights the ongoing challenge of generating valid JSON strings consistently.

Subsequently, we propose Schema Reinforcement Learning (SRL), an innovative training pipeline that integrates reinforcement learning with

<sup>&</sup>lt;sup>1</sup>https://www.json.org/



Figure 1: Overview of the data curation pipeline. We conduct multi-stage cleaning to obtain valid JSON schemas. The pie chart on the top right shows the data type distribution of the collected schemas. The top three data types are string, object, and array. The error cases in the left corner show possible errors models could make when generating JSON strings according to the given schema.

a fine-grained schema validator to enhance the model's ability to generate structured data. Furthermore, drawing inspiration from Chain-of-Thought (CoT) reasoning (Wei et al., 2022), we introduce a novel concept called Thought of Structure (ToS) within our training pipeline, which encourages the model to engage in deeper reasoning before generating specific JSON strings, guiding it to more effectively navigate complex structures. Interestingly, we also observe that, unlike regular fine-tuning, reinforcement learning helps the model maintain its general capabilities more effectively, preserving broader functionality even as it becomes more specialized in structured generation.

091

100

102

105

106

107

108

Finally, we evaluate the performance of the fine-tuned models in downstream tasks, such as BFCL (Yan et al., 2024), to validate the generalization of our approach. The results indicate that our model exhibits significant performance enhancements when calling tools in JSON format under specified schemas.

Our primary contributions are as follows:

- We introduce a benchmark of approximately 40K diverse JSON schemas to facilitate rigorous evaluation of model capabilities in structured output generation.
- We propose a novel training framework with online schema reinforcement learning, achieving up to 16% improvement in valid complex

JSON generation rates compared to supervised all baselines. 109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

• We demonstrate the practical efficacy of our approach through enhanced performance on downstream benchmarks such as BFCL, showing that improvements in structured generation translate directly to superior tasks without compromising general capabilities.

# 2 Related Work

The advancement of large language models (LLMs) has significantly expanded their applications across domains such as coding (Nam et al., 2024), writing (Pal et al., 2024), and automation (Zhu et al., 2023). A key aspect of these tasks is generating content in predefined formats, with JSON being one of the most widely used formats for structured data exchange, configuration, and API interaction.

One approach for structured JSON generation involves direct prompting with a JSON schema (Pokrass et al., 2024), where the model is asked to generate valid JSON. While effective for models with native JSON support, those without it often struggle to capture complex schema relationships, resulting in broken or incomplete JSON. To address these limitations, constrained generation methods have been proposed. For example, Outlines (Willard and Louf, 2023) restrict the model's predictions to a set of valid tokens, improving schema adherence. Techniques like SGLang (Zheng et al., 2024) and XGrammar (Dong et al., 2024) further enhance this by improving decoding efficiency. However, these methods can degrade output quality, particularly with complex schemas (Tam et al., 2024; He et al., 2024). Additionally, tool call re-parsing (Schick et al., 2023; Qin et al., 2023b,c; Qian et al., 2024) can help generate valid JSON by converting tool outputs, but this often requires significant post-processing and struggles to align with standard schemas, leading to inconsistencies.

While there are benchmarks (Zhou et al., 2023;
Chen et al., 2024; Xia et al., 2024; Wang et al., 2025) for evaluating structured generation, they typically focus on simpler schemas and lack a detailed analysis of how LLMs perform with complex JSON structures. This work aims to fill this gap by rigorously testing LLMs' ability to adhere to complex, nuanced JSON schemas.

# 3 SchemaBench

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

165

166

167

168

169

170

171

172

173

175

176

177

178

180

181

182

183

184

To construct the SchemaBench, we first introduce how we collect diverse schemas. Then we detailed how to create challenge tasks based on the schema we collected. Finally, we conduct a failure mode analysis to obtain an overview of problems when generating JSON strings with LLMs.

## 3.1 Data Collection

SchemaBench is designed to evaluate the structured output generation capabilities of large language models under realistic and complex schema constraints. To achieve that, we crawled a total of 108, 528 schema files from the JSON Schema Store<sup>2</sup> and GitHub. These schema files were selected to represent a wide range of applications, domains, and complexity levels, ensuring the diversity and representativeness of SchemaBench.

To focus on schemas that do not rely on external resources, we parsed any external URIs referenced within the schemas (both relative and absolute URI), filtering out those containing inaccessible external URIs and reducing the dataset to 46, 280 schemas. The relevant content from these URIs was then merged into the schemas, forming our basic schema data. Following this, we applied a rigorous filtering and validation process to ensure the schemas' compliance with JSON Schema syntax and conventions. As a result, we removed 5,574 schemas that did not meet these requirements. The remaining schemas were then divided into a training set and a test set, containing 36,960 and 3,746 schemas, respectively, which were used for constructing the training and testing datasets.

185

186

187

188

189

190

191

192

193

194

195

196

198

199

200

201

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

227

228

229

230

231

232

233

There are two main task categories in the SchemaBench: **Schema-only Generation** involves providing the model with a given schema and evaluating its ability to generate valid JSON strings that comply with the specified schema, including any embedded instructions. **Schemaconstrained Reasoning** requires the model to generate answers to a given question based on the schema, assessing the model's reasoning abilities while ensuring its output adheres to the schema. Next, we detailed the construction of each task.

#### 3.2 Schema-only Generation

The Schema-only Generation task evaluates LLMs' ability to generate structured output that strictly follows a given schema. We identified three key challenges, each addressed by a specific sub-task. The first, Complex Schema, tests the model's ability to navigate intricate schemas with references and logical compositions. This forms the foundation for models to generate valid JSON strings based on complex schemas. The second, Custom Formats, focuses on interpreting natural language instructions in schema descriptions, requiring models to follow custom formatting rules commonly found in real-world applications. The third, Escape Translation, challenges the model to generate valid JSON strings, correctly handling control characters and escape sequences, a more difficult task than simply adhering to the schema. Failure to properly handle these characters renders the entire JSON string invalid, making post-processing difficult. Figure 2 shows representative snippet of each sub-task.

**Complex Schema.** This task requires LLMs to generate a valid JSON string under the constraint of a given schema, which is a fundamental ability in schema-constrained generation scenarios. In this task, LLMs will be provided with a schema and asked to generate a valid JSON string for it. During validation, we first check whether the output string is a valid JSON. If the string is valid, we then use the Python jsonschema library to verify if the generated JSON string strictly adheres to the provided schema constraints.

Custom Formats. This task involves modify-

<sup>&</sup>lt;sup>2</sup>https://www.schemastore.org/json/



Figure 2: Top: snippets for three sub-tasks in **Schema-only Generation**. The last two snippets are special fields inserted into basic schemas like the first snippet. Bottom: corresponding common failure cases for three sub-tasks. The first one violates minLength requirement, the second one gives an incorrect base64 string and the third one gives a wrong number of backslash, causing escape error.

ing specific fields in the original schema to adhere to specialized rules, such as phone numbers, file paths (for Linux or Windows), strong password criteria, RGB color codes, base64-encoded strings, or other custom constraints. These rules, expressed as flexible, non-strict guidelines in the field descriptions, go beyond typical JSON Schema specifications. The process first checks the JSON syntax and compliance with the schema, then validates field values based on their unique instructions. We insert const or pattern in the schema for validating those fields. If all checks pass, the response is considered correct.

**Escape Translation.** This sub-task tests the LLM's ability to properly handle and escape special characters in strings. The LLM is given a string with special characters that must be escaped correctly and then inserted into a randomly selected field within a nested schema. The evaluation focuses on whether the LLM generates a valid JSON string, as improper escaping can break its validity. It also verifies that the special string is correctly inserted into the designated field. This task highlights the challenge of managing escape sequences in JSON, where specific characters (e.g., \", \\, \n) must be escaped to maintain correct syntax. Mismanagement of these sequences can result in parsing errors, invalidating the entire output.

#### 3.3 Schema-constrained Reasoning

In addition to simply generating valid JSON strings that conform to schema constraints, real-world ap-

|                                     | Complex      | Custom          | Escape       |
|-------------------------------------|--------------|-----------------|--------------|
| Counts<br>- Train Set<br>- Test Set | 9,241<br>936 | 18,478<br>1,874 | 9,241<br>936 |
| Avg. Length                         | 35,515       | 48,562          | 53,557       |
| < 2K                                | 4,014        | 7,903           | 3,955        |
| < 4K                                | 6,916        | 13,783          | 6,875        |
| < 10K                               | 9,102        | 18,250          | 9,073        |
| Avg. Desc. Length                   | 18,342       | 26,973          | 28,319       |
| Avg. Depth                          | 17.3         | 16.3            | 16.9         |

Table 1: Distribution of the SchemaBench. We filtered a total of 40, 706 diverse schemas, with an average character length of 35, 754 and an average nesting depth of the schema is 16.7. We calculate the depth of the schema by counting the maximum depth of the schema definition. The average character length of the descriptions within these schemas is 25, 152.

plications often require LLMs to perform specific tasks. We conduct the schema-constrained reasoning test for two main reasons. Firstly, generating answers in JSON may hurt the models' performance (Tam et al., 2024). An ideal model should deliver the same performance while it generates in JSON. Second, by checking the correctness of the answer, we can assess the quality of the generated JSON, surpassing the trivial schema checkings. Thus we adapted several common reasoningfocused datasets into schema-constrained reasoning tasks, including GSM8K (Cobbe et al., 2021), MATH-500 (Hendrycks et al., 2021b), MMLU (Hendrycks et al., 2021a), and ARC-Challenge (Clark et al., 2018). We convert them to 266

268

269

272

273

274

276

277

278



Figure 3: Statics of failure case of four models. We calculate it on the subset of the SchemaBench. All models except GPT-40 still exhibit a relatively high JSON parsing error, indicating their lack of robustness in JSON generation.

test the model's reasoning capabilities while adhering to schema rules. A detailed description of the reasoning schemas can be found in Appendix A.

### 3.4 Failure Mode Analysis

281

285

288

289

294

297

301

302

304

310

313

314

To assess the limitations of current LLMs in JSON generation, we perform a comprehensive failure mode analysis. In this evaluation, we test four widely used models on the previously generated task, utilizing greedy decoding. The results are presented in Figure 3. GPT-40 (OpenAI et al., 2023) stands out to be the best model but still obtained 13% validation error and 8% parser error, which implies that it can fail to generate valid JSON strings occasionally. During the three open-sourced models we tested, we observed more parser errors compared with GPT-40, indicating that these models tend to produce unresolvable strings. Qwen-2.5 7B (Yang et al., 2024) turns out to be the best among the open-sourced models, with a validation error of 18%. LLaMA-3.2 3B (Meta, 2024) and MiniCPM-3 4B (Hu et al., 2024) seem to be struggling to generate a resolvable JSON string, with a relatively high parser error of 23% and 36%.

Another common failure for the models we tested is the data format errors, including pattern errors, type errors, and enum errors. These kinds of errors indicate that the model generates content with unexpected data. Specifically, all models seem to have the same level of pattern error of 5%, which is dangerously close to the patterns we included in our test set. This indicates that when we use a regex pattern in the JSON schema, these models could easily fail to follow it.

### 4 Schema Reinforcement Learning

A straightforward approach to improve models' ability to generate JSON outputs is to conduct SFT. However, in practice, we encounter a significant challenge: the absence of high-quality, valid JSON strings that conform to the schemas we've collected. In constructing the training set for SchemaBench, we explored several methods to obtain such JSON samples, including using automatic JSON generators and model-based prompting, as shown in Figure 1. Unfortunately, neither approach was effective for generating JSON outputs that adhered to complex schemas at scale.

Therefore, instead of relying solely on manually curated datasets, we propose Schema Reinforcement Learning (SRL) by leveraging the model itself to generate the required valid JSON strings during training, allowing it to iteratively improve its performance in generating structured data. Building upon the framework presented in PRIME (Cui et al., 2025), we incorporate an online reinforcement learning approach to enhance the model's performance further.

Our algorithm is structured into three main phases, with each phase serving a specific purpose. In the sampling phase, we begin by generating Kresponses for each query in the dataset using the policy model  $\pi_{\theta}$ . Next, in the rewarding phase, we assess the quality of each response by obtaining rewards from both the schema validator  $r_s$  and the reward model  $r_{\phi}$ . Finally, in the updating phase, we update both the reward model  $r_{\phi}$  and the policy model  $\pi_{\theta}$ , and then initiate the next step in the process. Here we explain each phase in detail:

**Sampling Phase.** During the sampling phase, we reuse the tasks defined in SchemaBench as task templates and generate diverse responses from the model. Each task is sampled multiple times to identify the most appropriate task for the current training objectives.

Building on Chain-of-Thought (Wei et al., 2022),

352

353

317

318

319

320

403 404

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

we introduce Thoughts of Structure (ToS), where the model reflects on the structure while generating JSON strings. This is particularly useful for generating complex JSON objects, which may involve intricate schemas, nested structures, or conditional dependencies. ToS works by training the model to generate JSON5 strings<sup>3</sup> that include reasoning comments before the JSON output. During training, comments outline reasoning steps for each key-value pair, helping guide the generation process. During validation, these comments are ignored, and only the final JSON is validated.

**Rewarding Phase.** In this phase, we obtain rewards from the reward model and combine them with scores from the schema validator to estimate the advantages of each response. The advantage for the *i*-th response is computed as follows:

370

371

372

374

376

377

381

394

400

$$A^{i} = r(\mathbf{y}_{i}) - \frac{1}{K-1} \sum_{j \neq i} r(\mathbf{y}_{j})$$
(1)

where  $A^i$  represents the estimated advantage of the i-th response, and  $r(\mathbf{y}_i)$  is the reward score for the response  $\mathbf{y}_i$ . We use a leave-one-out estimation to calculate the advantage by comparing the reward of the current response to the average reward of all other responses. We sum up the advantage from the reward model and the validator to obtain the final advantages.

A naive approach would involve directly using the schema to validate the generated JSON, treating its correctness as the reward. However, as Figure 2 shows, the sensitivity of JSON formatting makes its reward signal sparse and challenging to optimize effectively. To address this, we introduce a more fine-grained schema validator that provides a detailed reward signal. This validator calculates the correctness ratio, defined as the proportion of correct tokens out of the total number of tokens in the generated string. In cases where the generated string is only partially valid, the validator computes the correctness ratio for the valid portion of the string. If the string fails to parse as a valid JSON object-due to missing brackets, commas, or other syntax issues-we split the string at the error position and pad with control characters to validate the remaining content.

**Updating Phase.** After obtaining rewards from the validator and reward model, we are ready to

update the reward model  $r_{\phi}$  and policy model  $\pi_{\theta}$ . Following PRIME, we select Cross Entropy loss to update the reward model and use PPO (Schulman et al., 2017) to update the policy model:

$$L_{\text{clip}}(\theta) = E[\min(\frac{\pi_{\theta}(y|\mathbf{y})}{\pi_{\theta_{\text{old}}}(y|\mathbf{y})}A, \\ \text{clip}(\frac{\pi_{\theta}(y|\mathbf{y})}{\pi_{\theta_{\text{old}}}(y|\mathbf{y})}, 1 - \epsilon, 1 + \epsilon)A)]$$
(2)

where  $\epsilon$  controls the clipping range, ensuring that the policy update remains within a safe region.

# **5** Experiments

In this section, we first analyze the detailed performance of the JSON schema following the capabilities of different models on SchemaBench. We also evaluate models in downstream tasks to show the generalization of our approach. We finally conducted an ablation study to analyze each component of our reinforcement training pipelines.

# 5.1 Schema-Related Capabilities Analysis

Settings. There are two main categories of testing in SchemaBench: schema-only generation and schema-constrained reasoning. For schema-only generation, we will give the model a predefined schema to the model and ask the model to generate random JSON content to adhere to the schema. Once they generate the content, we parse it and validate it with jsonschema<sup>4</sup> library. We use greedy decoding during the evaluation, and the prompts can be found in Appendix B. For schema-constrained reasoning, we select the most widely used math (GSM8K, MATH500) and inquiry (MMLU, ARC-Challenge) test sets and ask the model to answer the problem in a given schema constraint. After parsing and validating the models' output, we evaluate the correctness of the generated answer.

**Collected JSON** We selected several widelyused datasets to supplement our training data, which includes the following distribution: Ultra-Chat (Ding et al., 2023) (6k), UltraInteract (Yuan et al., 2024) (6k), xLAM (Liu et al., 2024b) (20k), Glaive<sup>5</sup> (20k) and ToolACE (Liu et al., 2024a) (10k). For the tool-calling datasets, we converted the provided tools into JSON schema format, requiring the model to output a valid JSON object

<sup>&</sup>lt;sup>3</sup>JSON5 is an extension to JSON, more details can be found at https://json5.org/.

<sup>&</sup>lt;sup>4</sup>https://github.com/python-jsonschema/ jsonschema

<sup>&</sup>lt;sup>5</sup>https://huggingface.co/datasets/glaiveai/ glaive-function-calling-v2/

|                      | Se      | chema-only | Generatior | ı       | Schema-constrained Reasoning |                |       | ng    |
|----------------------|---------|------------|------------|---------|------------------------------|----------------|-------|-------|
| Model                | Complex | Custom     | Escape     | Overall | GSM8K                        | <b>MATH500</b> | MMLU  | ARC-C |
| GPT-40               | 84.47   | 61.56      | 37.14      | 61.06   | 97.80                        | 41.40          | 86.16 | 97.01 |
| GPT-40-mini          | 68.86   | 46.17      | 16.89      | 43.98   | 86.13                        | 31.80          | 49.41 | 77.65 |
| Qwen-2.5 7B          | 72.42   | 43.60      | 11.11      | 42.38   | 94.54                        | 38.60          | 74.43 | 91.21 |
| MiniCPM-3 4B         | 53.88   | 20.29      | 9.13       | 27.77   | 69.22                        | 33.40          | 66.58 | 88.31 |
| LLaMA-3.1 8B         | 64.26   | 33.07      | 12.02      | 36.45   | 95.91                        | 85.60          | 71.83 | 84.98 |
| LLaMA-3.1 8B SFT     | 74.56   | 46.64      | 60.58      | 60.59   | 89.46                        | 63.80          | 66.97 | 84.56 |
| - w/o Collected JSON | 70.84   | 42.06      | 60.35      | 57.75   | 78.39                        | 46.00          | 58.87 | 75.68 |
| LLaMA-3.2 3B         | 49.84   | 27.31      | 8.37       | 28.51   | 80.97                        | 35.40          | 62.38 | 79.27 |
| LLaMA-3.2 3B SFT     | 71.71   | 45.52      | 52.21      | 56.48   | 82.94                        | 44.40          | 61.50 | 78.41 |
| - w/o Collected JSON | 72.42   | 42.83      | 54.82      | 56.69   | 78.85                        | 36.20          | 59.11 | 75.68 |
| LLaMA-3.2 3B SRL     | 82.25   | 66.13      | 69.10      | 72.50   | 84.23                        | 43.20          | 57.99 | 78.24 |

Table 2: Performance comparison of various models in SchemaBench, all presented in percentage. We compare two different training strategies: One is fine-tuning with the collected data, and the other conducts reinforcement learning on the train set of SchemaBench.

that adheres to the corresponding tool schema. Details of the conversion process and prompts can be found in Appendix C.

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

Results. Here, we present the performance of models in Table 2. For complex schema adherence, GPT-40 performs well, achieving 84.47%, demonstrating strong JSON schema compliance. However, the best model for the escape translation test is still GPT-40, though it only scores 37.14%, revealing the difficulty in handling complex content generation. For the open-sourced models, the Qwen-2.5 7B stands out to be the best, reaching up to 72.42% in complex schema tests.

After fine-tuning on the SchemaBench, models show significant improvements in schema-only generation tasks. Notably, the LLaMA-3.2 3B model obtained a remarkable boost, increasing from 28.51% to 72.50% after SRL, outperforming both the SFT version and all other models. The LLaMA-3.1 8B model also improved, with SFT increasing performance from 36.45% to 60.59%, rivaling GPT-40. Fine-tuning LLaMA models without Collected JSON, however, led to performance drops, which means models can hardly generalize their schema-following ability to schemaconstrained reasoning tasks. In contrast, we surprisingly find that the model's performance could generalize better during SRL.

#### 5.2 Downstream Tasks Analysis

Here, we use BFCL (Yan et al., 2024) to measure
models' performance on downstream JSON generation tasks. We modified its tasks by using JSON
schema to constrain the models' output. The de-

tailed prompt we use can be found in Appendix C.

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

**Results.** The performance of models on downstream tasks is summarized in Table 3. For BFCL-Live, LLaMA-3.1 8B and LLaMA-3.2 3B perform poorly in most categories using tools in JSON, with some categories scoring 0.00%. This is due to their inability to handle complex tool-calling schemas. However, after fine-tuning, both models show significant improvement, adapting to schema constraints and achieving better performance. For the Irrelevance and Relevance metrics, the original LLaMA models struggle with generating valid tool calls, leading to high Irrelevance and low Relevance scores. After fine-tuning, LLaMA-3.2 3B achieves 97.56% Relevance and 47.20% Irrelevance, demonstrating improved tool call generation and schema adherence. The LLaMA-3.2 3B SRL demonstrates its superiority once again, achieving an impressive score of 57.00%, even in the absence of a ground truth answer.

#### 5.3 Ablation Study

In this section, we compare different settings for schema reinforcement training and how it impacts the performance of structured generation.

**Settings.** Across all settings, we take the same training pipelines as detailed in Section 4. We use the training set of the SchemaBench to train our models, which contain around 37K different schemas. We evaluate models on the test set of the SchemaBench. We conducted experiments to find whether adding ToS or the fine-grained schema validator (F.G-val) could impact the performance of the models. We set a batch size of 32 and a

|                            |        |          |          | <b>BFCL-Live</b>  |             |           |   |
|----------------------------|--------|----------|----------|-------------------|-------------|-----------|---|
| Model                      | Simple | Multiple | Parallel | Multiple Parallel | Irrelevance | Relevance | Overall   |
| GPT-4o Tool Callings       | 36.43  | 37.22    | 18.75    | 41.67             | 94.40       | 29.27     | 59.13   |
| Qwen-2.5 7B                | 69.77  | 75.41    | 0.00     | 0.00              | 48.23       | 95.12     | 63.22   |
| Qwen-2.5 7B Tool Callings  | 57.36  | 57.67    | 12.50    | 33.33             | 45.26       | 82.93     | 52.69   |
| LLaMA-3.1 8B               | 0.39   | 0.00     | 0.00     | 0.00              | 60.11       | 36.59     | 24.08   |
| LLaMA-3.1 8B Tool Callings | 65.12  | 63.35    | 50.00    | 50.00             | 37.26       | 80.49     | 53.62   |
| LLaMA-3.1 8B SFT           | 72.09  | 68.76    | 50.00    | 66.67             | 25.49       | 97.56     | 52.69   |
| LLaMA-3.2 3B               | 4.26   | 13.11    | 0.00     | 0.00              | 73.26       | 39.02     | 35.72           52.69           64.10           57.00 |
| LLaMA-3.2 3B Tool Callings | 57.36  | 57.67    | 12.50    | 33.33             | 45.26       | 82.93     |   |
| LLaMA-3.2 3B SFT           | 74.03  | 74.64    | 68.75    | 58.33             | 47.20       | 97.56     |   |
| LLaMA-3.2 3B SRL           | 65.50  | 64.22    | 50.00    | 29.17             | 45.03       | 95.12     |   |

Table 3: Performance comparison of various models in the downstream JSON generation task. We select the live part of the BFCL to make sure the score is valid. The tool calling lines stand for the performance in the official tool calling formats. The fine-tuned model and the model enhanced with reinforcement training all show performance improvements. The overall score is calculated on the weighted average score of all live tests.

| Settings       | Schema | <b>MATH-500</b> | ARC-C |
|----------------|--------|-----------------|-------|
| LLaMA-3.2 3B   | 28.51  | 35.40           | 79.27 |
| trained w/ ORM | 31.15  | 39.40           | 78.92 |
| + ToS          | 44.89  | 36.60           | 80.38 |
| + F.G-val      | 35.59  | 35.60           | 79.10 |

Table 4: Ablation study results for LLaMA-3.2 3B. For each line, we train the model by adding a component into the ordinary RL pipelines with an outcome verifier. All results are reported with RL after 10K samples.

learning rate of  $5e^{-7}$  for all experiments. We run all experiments with 10K sampling times.

510

511

512

513

515

516

518

519

520

522

524

526

527

528

**Results.** As Figure 4 shows, by providing finegrained evaluation results, the model shows a consistent improvement across the training process, demonstrating the effectiveness of our training methods. We also find that the reinforcement training is quite efficient compared with supervised fine-tuning, easily outperforming the baseline when halfway through training.

Table 4 demonstrate the effectiveness of each component for the training. Compared with the original model, the model training with ORM improves from 28.51% to 31.15% on the SchemaBench, demonstrating the effectiveness of reinforcement training. Adding ToS into training dramatically improves the performance, reaching up to 44.89% in the complex schema following. The fine-grained validator shows its superior performance when compared witthe h trivial outcome validator, with a performance up to 35.59% in testing. Besides, we also observed that across all settings, the performance on MATH-500 and ARC-C



Figure 4: Reinforcement training accuracy on complex schema subset for LLaMA-3.2 3B. The red line is the fine-tuning baseline.

obtained certain improvements. We consider this to be a benefit from the escaping training, which reduces the parsing error and brings improvements.

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

## 6 Conculsion

This study introduces the SchemaBench benchmark to evaluate model performance in generating valid JSON strings for complex schemas. Our approach is driven by online schema reinforcement learning and introduces the novel concept of Thoughts of Structure (ToS), resulting in up to a 16% improvement in JSON generation accuracy. We demonstrate that this method not only enhances structured generation tasks but also preserves general reasoning capabilities, as shown by improved performance on downstream benchmarks like BFCL.

563

564

565

566

568

569

570

571

572

573

577

585 586

588

589

590

593

## Ethical Statement

547 We honor the Code of Ethics and we strictly fol548 lowed ethical standards in the construction of our
549 dataset. No private data or non-public information
550 is used in our work.

## 551 Limitation

This work has two limitations. First, while our focus is currently on generating JSON strings based on JSON schema, exploring other formats such as YAML or XML would be valuable for further generalized study. Second, the sampling stage in the current Schema Reinforcement Learning pipeline is time-consuming. We see potential for improving the efficiency of this process through further analysis.

## References

- Jiangong Chen, Xiaoyi Wu, Tian Lan, and Bin Li. 2025. Llmer: Crafting interactive extended reality worlds with json data generated by large language models. *arXiv preprint arXiv:2502.02441*.
  - Yihan Chen, Benfeng Xu, Quan Wang, Yi Liu, and Zhendong Mao. 2024. Benchmarking large language models on controllable generation under diversified instructions. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 17808– 17816.
  - Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. 2022. Palm: Scaling language modeling with pathways. *ArXiv preprint*, abs/2204.02311.
  - Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv:1803.05457v1*.
  - Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.
  - Ganqu Cui, Lifan Yuan, Zefan Wang, Hanbin Wang, Wendi Li, Bingxiang He, Yuchen Fan, Tianyu Yu, Qixin Xu, Weize Chen, Jiarui Yuan, Huayu Chen, Kaiyan Zhang, Xingtai Lv, Shuo Wang, Yuan Yao, Xu Han, Hao Peng, Yu Cheng, Zhiyuan Liu, Maosong Sun, Bowen Zhou, and Ning Ding. 2025. Process reinforcement through implicit rewards.

Ning Ding, Yulin Chen, Bokai Xu, Yujia Qin, Shengding Hu, Zhiyuan Liu, Maosong Sun, and Bowen Zhou. 2023. Enhancing chat language models by scaling high-quality instructional conversations. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 3029–3051, Singapore. Association for Computational Linguistics. 595

596

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

- Yixin Dong, Charlie F. Ruan, Yaxing Cai, Ruihang Lai, Ziyi Xu, Yilong Zhao, and Tianqi Chen. 2024. Xgrammar: Flexible and efficient structured generation engine for large language models.
- Miguel Escarda-Fernández, Iñigo López-Riobóo-Botana, Santiago Barro-Tojeiro, Lara Padrón-Cousillas, Sonia Gonzalez-Vázquez, Antonio Carreiro-Alonso, and Pablo Gómez-Area. 2024. Llms on the fly: Text-to-json for custom api calling. *Proceedings of the SEPLN-CEDI*.
- Jia He, Mukund Rungta, David Koleczek, Arshdeep Sekhon, Franklin X Wang, and Sadid Hasan. 2024. Does prompt formatting have any impact on llm performance?
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021a. Measuring massive multitask language understanding. *Proceedings of the International Conference on Learning Representations (ICLR)*.
- Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021b. Measuring mathematical problem solving with the math dataset. *NeurIPS*.
- Shengding Hu, Yuge Tu, Xu Han, Chaoqun He, Ganqu Cui, Xiang Long, Zhi Zheng, Yewei Fang, Yuxiang Huang, Weilin Zhao, et al. 2024. Minicpm: Unveiling the potential of small language models with scalable training strategies. *arXiv preprint arXiv:2404.06395*.
- Weiwen Liu, Xu Huang, Xingshan Zeng, Xinlong Hao, Shuai Yu, Dexun Li, Shuai Wang, Weinan Gan, Zhengying Liu, Yuanqing Yu, Zezhong Wang, Yuxian Wang, Wu Ning, Yutai Hou, Bin Wang, Chuhan Wu, Xinzhi Wang, Yong Liu, Yasheng Wang, Duyu Tang, Dandan Tu, Lifeng Shang, Xin Jiang, Ruiming Tang, Defu Lian, Qun Liu, and Enhong Chen. 2024a. Toolace: Winning the points of llm function calling.
- Zuxin Liu, Thai Hoang, Jianguo Zhang, Ming Zhu, Tian Lan, Shirley Kokane, Juntao Tan, Weiran Yao, Zhiwei Liu, Yihao Feng, Rithesh Murthy, Liangwei Yang, Silvio Savarese, Juan Carlos Niebles, Huan Wang, Shelby Heinecke, and Caiming Xiong. 2024b. Apigen: Automated pipeline for generating verifiable and diverse function-calling datasets.
- Meta. 2024. Introducing meta llama 3: The most capable openly available llm to date.

- 649 650
- 651

664

665

674

675

676

677

685

705

710

711

Daye Nam, Andrew Macvean, Vincent Hellendoorn, Bogdan Vasilescu, and Brad Myers. 2024. Using an Ilm to help with code understanding. In *Proceedings* of the IEEE/ACM 46th International Conference on Software Engineering, pages 1–13.

OpenAI, :, Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, Red Avila, Igor Babuschkin, Suchir Balaji, Valerie Balcom, Paul Baltescu, Haiming Bao, Mo Bavarian, Jeff Belgum, Irwan Bello, Jake Berdine, Gabriel Bernadett-Shapiro, Christopher Berner, Lenny Bogdonoff, Oleg Boiko, Madelaine Boyd, Anna-Luisa Brakman, Greg Brockman, Tim Brooks, Miles Brundage, Kevin Button, Trevor Cai, Rosie Campbell, Andrew Cann, Brittany Carey, Chelsea Carlson, Rory Carmichael, Brooke Chan, Che Chang, Fotis Chantzis, Derek Chen, Sully Chen, Ruby Chen, Jason Chen, Mark Chen, Ben Chess, Chester Cho, Casey Chu, Hyung Won Chung, Dave Cummings, Jeremiah Currier, Yunxing Dai, Cory Decareaux, Thomas Degry, Noah Deutsch, Damien Deville, Arka Dhar, David Dohan, Steve Dowling, Sheila Dunning, Adrien Ecoffet, Atty Eleti, Tyna Eloundou, David Farhi, Liam Fedus, Niko Felix, Simón Posada Fishman, Juston Forte, Isabella Fulford, Leo Gao, Elie Georges, Christian Gibson, Vik Goel, Tarun Gogineni, Gabriel Goh, Rapha Gontijo-Lopes, Jonathan Gordon, Morgan Grafstein, Scott Gray, Ryan Greene, Joshua Gross, Shixiang Shane Gu, Yufei Guo, Chris Hallacy, Jesse Han, Jeff Harris, Yuchen He, Mike Heaton, Johannes Heidecke, Chris Hesse, Alan Hickey, Wade Hickey, Peter Hoeschele, Brandon Houghton, Kenny Hsu, Shengli Hu, Xin Hu, Joost Huizinga, Shantanu Jain, Shawn Jain, Joanne Jang, Angela Jiang, Roger Jiang, Haozhun Jin, Denny Jin, Shino Jomoto, Billie Jonn, Heewoo Jun, Tomer Kaftan, Łukasz Kaiser, Ali Kamali, Ingmar Kanitscheider, Nitish Shirish Keskar, Tabarak Khan, Logan Kilpatrick, Jong Wook Kim, Christina Kim, Yongjik Kim, Hendrik Kirchner, Jamie Kiros, Matt Knight, Daniel Kokotajlo, Łukasz Kondraciuk, Andrew Kondrich, Aris Konstantinidis, Kyle Kosic, Gretchen Krueger, Vishal Kuo, Michael Lampe, Ikai Lan, Teddy Lee, Jan Leike, Jade Leung, Daniel Levy, Chak Ming Li, Rachel Lim, Molly Lin, Stephanie Lin, Mateusz Litwin, Theresa Lopez, Ryan Lowe, Patricia Lue, Anna Makanju, Kim Malfacini, Sam Manning, Todor Markov, Yaniv Markovski, Bianca Martin, Katie Mayer, Andrew Mayne, Bob McGrew, Scott Mayer McKinney, Christine McLeavey, Paul McMillan, Jake McNeil, David Medina, Aalok Mehta, Jacob Menick, Luke Metz, Andrey Mishchenko, Pamela Mishkin, Vinnie Monaco, Evan Morikawa, Daniel Mossing, Tong Mu, Mira Murati, Oleg Murk, David Mély, Ashvin Nair, Reiichiro Nakano, Rajeev Nayak, Arvind Neelakantan, Richard Ngo, Hyeonwoo Noh, Long Ouyang, Cullen O'Keefe, Jakub Pachocki, Alex Paino, Joe Palermo, Ashley Pantuliano, Giambattista Parascandolo, Joel Parish, Emy Parparita, Alex Passos, Mikhail Pavlov, Andrew Peng, Adam Perelman, Filipe de Avila Belbute Peres, Michael Petrov,

Henrique Ponde de Oliveira Pinto, Michael, Pokorny, Michelle Pokrass, Vitchyr Pong, Tolly Powell, Alethea Power, Boris Power, Elizabeth Proehl, Raul Puri, Alec Radford, Jack Rae, Aditya Ramesh, Cameron Raymond, Francis Real, Kendra Rimbach, Carl Ross, Bob Rotsted, Henri Roussez, Nick Ryder, Mario Saltarelli, Ted Sanders, Shibani Santurkar, Girish Sastry, Heather Schmidt, David Schnurr, John Schulman, Daniel Selsam, Kyla Sheppard, Toki Sherbakov, Jessica Shieh, Sarah Shoker, Pranav Shyam, Szymon Sidor, Eric Sigler, Maddie Simens, Jordan Sitkin, Katarina Slama, Ian Sohl, Benjamin Sokolowsky, Yang Song, Natalie Staudacher, Felipe Petroski Such, Natalie Summers, Ilya Sutskever, Jie Tang, Nikolas Tezak, Madeleine Thompson, Phil Tillet, Amin Tootoonchian, Elizabeth Tseng, Preston Tuggle, Nick Turley, Jerry Tworek, Juan Felipe Cerón Uribe, Andrea Vallone, Arun Vijayvergiya, Chelsea Voss, Carroll Wainwright, Justin Jay Wang, Alvin Wang, Ben Wang, Jonathan Ward, Jason Wei, CJ Weinmann, Akila Welihinda, Peter Welinder, Jiavi Weng, Lilian Weng, Matt Wiethoff, Dave Willner, Clemens Winter, Samuel Wolrich, Hannah Wong, Lauren Workman, Sherwin Wu, Jeff Wu, Michael Wu, Kai Xiao, Tao Xu, Sarah Yoo, Kevin Yu, Qiming Yuan, Wojciech Zaremba, Rowan Zellers, Chong Zhang, Marvin Zhang, Shengjia Zhao, Tianhao Zheng, Juntang Zhuang, William Zhuk, and Barret Zoph. 2023. Gpt-4 technical report. Technical report.

712

713

714

715

716

719

720

721

722

723

724

725

726

727

729

730

732

733

734

735

736

737

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

768

769

- Soumen Pal, Manojit Bhattacharya, Md Aminul Islam, and Chiranjib Chakraborty. 2024. Ai-enabled chatgpt or llm: a new algorithm is required for plagiarismfree scientific writing. *International Journal of Surgery*, 110(2):1329–1330.
- Michelle Pokrass, Chris Colby, Melody Guan, Ted Sanders, and Brian Zhang. 2024. Introducing structured outputs in the api. Acknowledgments: John Allard, Filipe de Avila Belbute Peres, Ilan Bigio, Owen Campbell-Moore, Chen Ding, Atty Eleti, Elie Georges, Katia Gil Guzman, Jeff Harris, Johannes Heidecke, Beth Hoover, Romain Huet, Tomer Kaftan, Jillian Khoo, Karolis Kosas, Ryan Liu, Kevin Lu, Lindsay McCallum, Rohan Nuttall, Joe Palermo, Leher Pathak, Ishaan Singal, Felipe Petroski Such, Freddie Sulit, David Weedon.
- Chen Qian, Xin Cong, Wei Liu, Cheng Yang, Weize Chen, Yusheng Su, Yufan Dang, Jiahao Li, Juyuan Xu, Dahai Li, Zhiyuan Liu, and Maosong Sun. 2023. Communicative agents for software development.
- Cheng Qian, Chenyan Xiong, Zhenghao Liu, and Zhiyuan Liu. 2024. Toolink: Linking toolkit creation and using through chain-of-solving on open-source model. In Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers), pages 831–854, Mexico City, Mexico. Association for Computational Linguistics.

Yujia Qin, Zihan Cai, Dian Jin, Lan Yan, Shihao Liang, Kunlun Zhu, Yankai Lin, Xu Han, Ning Ding, Huadong Wang, Ruobing Xie, Fanchao Qi, Zhiyuan Liu, Maosong Sun, and Jie Zhou. 2023a. WebCPM: Interactive web search for Chinese long-form question answering. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8968–8988, Toronto, Canada. Association for Computational Linguistics.

771

780

781

784

790

791

792

793

796

799

800

801

802

806

810

811

812

813

814

815

816

817

818

819

821

822 823

824

826

827

- Yujia Qin, Shengding Hu, Yankai Lin, Weize Chen, Ning Ding, Ganqu Cui, Zheni Zeng, Yufei Huang, Chaojun Xiao, Chi Han, et al. 2023b. Tool learning with foundation models. *ArXiv preprint*, abs/2304.08354.
- Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, Dahai Li, Zhiyuan Liu, and Maosong Sun. 2023c. Toolllm: Facilitating large language models to master 16000+ real-world apis.
- Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023.
  Toolformer: Language models can teach themselves to use tools. In Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023.
- John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.
- Zhi Rui Tam, Cheng-Kuang Wu, Yi-Lin Tsai, Chieh-Yen Lin, Hung-yi Lee, and Yun-Nung Chen. 2024. Let me speak freely? a study on the impact of format restrictions on large language model performance. In Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing: Industry Track, pages 1218–1236.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023. Llama: Open and efficient foundation language models.
- Zhaoyang Wang, Jinqi Jiang, Huichi Zhou, Wenhao Zheng, Xuchao Zhang, Chetan Bansal, and Huaxiu Yao. 2025. Verifiable format control for large language model generations.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022.

Brandon T Willard and Rémi Louf. 2023. Efficient guided generation for llms. *arXiv preprint arXiv:2307.09702*.

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

- Congying Xia, Chen Xing, Jiangshu Du, Xinyi Yang, Yihao Feng, Ran Xu, Wenpeng Yin, and Caiming Xiong. 2024. Fofo: A benchmark to evaluate llms' format-following capability.
- Fanjia Yan, Huanzhi Mao, Charlie Cheng-Jie Ji, Tianjun Zhang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. 2024. Berkeley function calling leaderboard.
- An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, et al. 2024. Qwen2 technical report. *arXiv preprint arXiv:2407.10671*.
- Lifan Yuan, Ganqu Cui, Hanbin Wang, Ning Ding, Xingyao Wang, Jia Deng, Boji Shan, Huimin Chen, Ruobing Xie, Yankai Lin, Zhenghao Liu, Bowen Zhou, Hao Peng, Zhiyuan Liu, and Maosong Sun. 2024. Advancing llm reasoning generalists with preference trees.
- Aohan Zeng, Xiao Liu, Zhengxiao Du, Zihan Wang, Hanyu Lai, Ming Ding, Zhuoyi Yang, Yifan Xu, Wendi Zheng, Xiao Xia, Weng Lam Tam, Zixuan Ma, Yufei Xue, Jidong Zhai, Wenguang Chen, Zhiyuan Liu, Peng Zhang, Yuxiao Dong, and Jie Tang. 2023.
  GLM-130B: an open bilingual pre-trained model. In The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023. OpenReview.net.
- Lianmin Zheng, Liangsheng Yin, Zhiqiang Xie, Chuyue Sun, Jeff Huang, Cody Hao Yu, Shiyi Cao, Christos Kozyrakis, Ion Stoica, Joseph E. Gonzalez, Clark Barrett, and Ying Sheng. 2024. Sglang: Efficient execution of structured language model programs.
- Jeffrey Zhou, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. 2023. Instruction-following evaluation for large language models. *arXiv preprint arXiv:2311.07911*.
- Chenxu Zhu, Bo Chen, Huifeng Guo, Hang Xu, Xiangyang Li, Xiangyu Zhao, Weinan Zhang, Yong Yu, and Ruiming Tang. 2023. Autogen: An automated dynamic model generation framework for recommender system. In *Proceedings of the Sixteenth ACM International Conference on Web Search and Data Mining*, pages 598–606.

```
876
```

# Appendix

# A Schema-constrained Reasoning

```
GSM8K:
{
    "type": "object",
    "properties":{
        "thought": {
            "type": "string",
            "description": "put your thought here"
        },
```

```
"required": ["thought", "answer"],
```

879

## MATH500:

},

}

{

```
"type": "object",
"properties":{
    "thought": {
        "type": "string",
        "description": "put your thought here"
    },
    "answer": {
        "type": "number",
        "description": "put your answer here"
    }
},
"required": ["thought", "answer"],
```

881

# MMLU:

}

```
{
    "type": "object",
    "properties": {
        "thought": {
            "type": "string",
            "description": "put your thought here"
        },
        "answer": {
            "type": "string",
            "type": "string",
            "type": "string",
            "type": "string",
            "type": "string",
            "type": "string",
            "type": "put your choice here"
        }
    },
    "required": ["thought", "answer"],
}
```

# ARC-Challenge:

{

```
"type": "object",
"properties": {
    "thought": {
        "type": "string",
        "description": "put your thought here"
    },
    "answer": {
        "type": "string",
        "description": "put your answer here,
        → Options only, e.g. A",
```

# **B** Benchmark Prompts

```
System prompt template:
```

"""You should generate answer with given JSON
→ format.
<Schema> Here are the json-schema of the content
→ format:
{schema}
</Schema>"""

| For Complex Schema and Custom Formats, the        | 884 |
|---|-----|
| user prompt is as follow:                         | 885 |
| "Please generate a valid JSON object according to |     |

882

883

886

887

888

889

890

891

→ the JSON schema. Give your JSON object according to
 → directly, without ```."
 User prompt in Escape Translation:

```
"Please generate a valid JSON object according to

→ the JSON schema, remember your special token

→ here: {special_token} Give your JSON object

→ directly, without ```."
```

As for tasks in Schema-constrained Reasoning, we simply use the query in dataset as the user prompt.

# C Tool Callings Conversion

```
We use the following code to convert tools to a formal JSON schema.
```

```
def convert_function_to_schema(functions):
  schema = {
    "$defs": {
      "tools": {
       "description": "Available tools you could
        \leftrightarrow use."
        "oneOf": []
     }
    },
  }
  for func in functions:
    # aligning informal types to standard JSON
    \hookrightarrow schema basic data types
    # e.g. 'dict' -> 'object', 'list' -> 'array'
    new_func = recurrsive_convert_type(func)
  schema["$defs"][func["name"]] = {
    "type": "object",
    "description": func.get("description", ""),
    "properties": {
     func["name"]: new_func["parameters"]
    },
    "required": [func["name"]],
    "additionalProperties": False
  }
  schema["$defs"]["tools"]["oneOf"].append({
  \rightarrow "$ref":
```

```
→ '~0').replace('/', '~1')) })
```

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

```
24
      schema["oneOf"] = [
       25
26
27
         → array.",
"items": {
    "$ref": "#/$defs/tools"
28
29
         },
30
         "minItems": 2
31
       },
32
33
       {
         "$ref": "#/$defs/tools"
34
35
       },
       36
37
38
         \, \hookrightarrow \, given question lacks the parameters
         \leftrightarrow required by the function, also point it
         \leftrightarrow out here."
       }
39
40
      ]
      jsonschema.Validator.check_schema(schema)
41
42
   return schema
```